

DAD-1 (19-0831) PREMIUM DESICCANT FOR DEVILBISS DAD-500 AND SHARPE 6760 AIR DRYING SYSTEMS

WARNING

Risk of Injury. Pressurized components. Relieve pressure before servicing. Risk of slipping. Sweep up spills immediately.

CAUTION

Avoid prolonged breathing of dust or contact with skin.

NOTE

Refer to the Service Bulletin for your system. The Material Safety Data sheet MSDS-1 is available on request.

DEVILBISS DAD-500 INSTRUCTIONS

FILLING NEW DESICCANT TANK

See Step 3 and Steps 8 to 11 below.

REPLACEMENT OF USED DESICCANT

Replace desiccant when sight glass indicator changes to pink or white. A non-adhesive sealant (PTFE pipe tape) is recommended on all pipe threads.

1. Relieve air pressure from the desiccant tank.
2. Place a container under desiccant tank. Remove bottom drain plug.
3. Remove top fill plug.

NOTE

Tank contains internal filters at inlet and outlet. Be careful not to damage these filters when changing desiccant.

4. With container still under tank, using a duster gun, blow out remaining desiccant.
5. Check internal filters and replace if damaged.
6. Remove sight glass using a socket or box wrench and replace indicator paper. Install sight glass.
7. Install bottom plug.
8. With small end of desiccant funnel bag pointed upwards, cut between the two lines.
9. Pour desiccant into top fill opening.

NOTE

Any small desiccant particles will adhere to the inside of the special bag. Do not pour any fine particles into tank.

10. Repeat with second bag. **Tank must be completely filled.** Use your gloved finger to gently push desiccant to the side to fill completely. Extra desiccant is provided. A small amount will be remaining in the bag.
11. Install top plug. The sight glass indicator should change to blue within 30 minutes.
12. The used desiccant can be disposed of according to local regulations for non-hazardous chemical disposal.

SHARPE 6760 INSTRUCTIONS

REPLACEMENT OF USED DESICCANT

Replace desiccant when sight glass indicator changes to pink or white. A non-adhesive sealant (PTFE pipe tape) is recommended on all pipe threads.

NOTE

The DAD-1 contains enough desiccant for TWO Sharpe refills.

1. Relieve air pressure from the desiccant tank.
2. Remove Stage 3 retaining ring and pour out desiccant.
3. Remove sight glass and insert indicator paper. Install sight glass.
4. With small end of desiccant funnel bag pointed upwards, cut between the two lines.
5. Pour one bag of desiccant into Stage 3 housing. After filling, it is normal for a 2" to 3" space to remain above the desiccant.

NOTE

Any small desiccant particles will adhere to the inside of the special bag. Do not pour any fine particles into tank.

6. Reinstall filled Stage 3 housing. Tighten ring securely.
7. The sight glass indicator should change to blue within 30 minutes.
8. The used desiccant can be disposed of according to local regulations.

WARRANTY POLICY

DeVilbiss products are covered by Finishing Brands one year materials and workmanship limited warranty. The use of any parts or accessories, from a source other than Finishing Brands, will void all warranties. For specific warranty information please contact the closest Finishing Brands location listed below.

Finishing Brands reserves the right to modify equipment specifications without prior notice. DeVilbiss®, Ransburg®, BGK®, and Binks® are registered trademarks of Carlisle Fluid Technologies, Inc., dba Finishing Brands. ©2015 Carlisle Fluid Technologies, Inc., dba Finishing Brands. All rights reserved.



DeVILBISS

DeVilbiss is part of Finishing Brands, a global leader in innovative spray finishing technologies. For technical assistance or to locate an authorized distributor, contact one of our international sales and customer support locations below.

USA/Canada

www.devilbiss.com
info@carlisleleft.com
Tel: 1-800-992-4657
Fax: 1-888-246-5732

Mexico

www.carlisleleft.com.mx
ventas@carlisleleft.com.mx
Tel: 011 52 55 5321 2300
Fax: 011 52 55 5310 4790

Brazil

www.devilbiss.com.br
vendas@carlisleleft.com.br
Tel: +55 11 5641 2776
Fax: 55 11 5641 1256

United Kingdom

www.finishingbrands.eu
info@carlisleleft.eu
Tel: +44 (0)1202 571 111
Fax: +44 (0)1202 573 488

France

www.finishingbrands.eu
info@carlisleleft.eu
Tel: +33(0)475 75 27 00
Fax: +33(0)475 75 27 59

Germany

www.finishingbrands.eu
info@carlisleleft.eu
Tel: +49 (0) 6074 403 1
Fax: +49 (0) 6074 403 281

China

www.finishingbrands.com.cn
mkt@carlisleleft.com.cn
Tel: +8621-3373 0108
Fax: +8621-3373 0308

Japan

www.ransburg.co.jp
overseas-sales@carlisleleft.co.jp
Tel: 081 45 785 6421
Fax: 081 45 785 6517

Australia

www.finishingbrands.com.au
sales@carlisleleft.com.au
Tel: +61 (0) 2 8525 7555
Fax: +61 (0) 2 8525 7500

DeVILBISS
AUTOMOTIVE REFINISHING

DeVilbiss Automotive Refinishing is part of Finishing Brands, a global leader in innovative spray finishing technologies. For technical assistance or to locate an authorized distributor, contact one of our sales and customer support locations below.

USA/Canada

www.autorefinishdevilbiss.com
askus@carlisleleft.com
Toll Free Tel: 1-800-445-3988
Toll Free Fax: 1-800-445-6643

Mexico

www.autorefinishdevilbiss.com.mx
Toll Free Tel: 1-888-835-6232 USA



DeVILBISS



Ransburg



BGK



BINKS



Finishing Brands®

A CARLISLE COMPANY