
# **DEVILBISS**

## **KB-428-1 REGULATOR KIT**



Used to repair - KB II style pressure cups or HARG-510 regulator.

### **KB-428-1 Regulator Kit Parts List**

Ref.		
No.	Description	Qty.
1	Bonnet & Adjusting Screw	/ 1
2	Regulating Spring	1
3	Slip Ring	1
4	Diaphragm, PTFE	1
5	Valve Seat & Gasket Assy.	1
6	Valve, PTFE	1
7	Valve Spring	1

WARNING

Risk of injury from pressurized components. Turn off inlet air pressure and bleed off remaining pressure before disassembly.

### SERVICE INSTRUCTION

#### DISASSEMBI V:

WARNING

Risk of injury from pressurized components. Turn off inlet air pressure and bleed off remaining pressure before disassembly.

- 1. Turn regulator knob counterclockwise until it stops.
- 2. Unscrew the bonnet (1) from the regulator body or pressure cup lid, remove adjusting screw & nut, then the regulating spring (2), slip ring (3) & diaphragm (4). Unscrew the valve seat and gasket assembly (5) using a screwdriver, then remove valve (6) and valve spring (7).

#### CLEANING

- 1. Clean parts using warm water and soap.
- 2. Inspect all parts.
- 3. Replace damaged parts.

#### REASSEMBLY:

- 1. At reassembly, apply a small amount of lubricant, Spray Gun Lube, to adjusting screw threads inside bonnet (1).
- 2. Torque valve seat (5) to 4-6 inch pounds. Torque bonnet (1) to 50-60 inch pounds.



DeVilbiss is part of Finishing Brands, a global leader in innovative spray finishing technologies. For technical assistance or to locate an authorized distributor, contact our sales and customer support location below.

#### USA/Canada Industrial Finishing www.devilbiss.com

info@carlisleft.com Tel: 1-800-992-4657

Fax: 1-888-246-5732



DeVilbiss Automotive Refinishing is part of Finishing Brands, a global leader in innovative spray finishing technologies. For technical assistance or to locate an authorized distributor, contact our sales and customer support location below.

#### USA/Canada

www.autorefinishdevilhiss.com askus@carlisleft.com

Toll Free Tel: 1-800-445-3988 Toll Free Fax: 1-800-445-6643